

SMB-23Z12F

12X Dahili Mini Speed Dome Kamera



Genel Özellikler

- 1/4" IT CCD Renklide 550 TvL/Siyah Beyazda 600 TvLine
- 3.68 mm - 43.53 mm lens F1.65(W)~F1.99(T)
- True Day&Night (ICR), 3D-DNR, X-WDR
- Pan/Tilt Hızı: 0.1° ~ 360°/sn Pan 360°, Tilt 90°
- Electronic Shutter: 1/50 ~ 1/90.000 sn
- RS-485 • IP66
- 144x Zoom, 12x Optik Zoom, 12x Digital Zoom
- 0.1 Lux(Renkli) / 0.0002Lux (S/B, DSS Açık)
- 127 preset Pozisyonu / 8 swing, 4 partion, 8 grup
- OSD, BLC, ECL, İris kontrol (1-100)
- Digital Slow Shutter
- AGC, AIC, AWB, BLC, ATW
- Flickerless - Titreşim önleme
- Otomatik Odaklanma, Oto parking Fonksiyonu
- Electric Flip Fonksiyonu
- Privacy Zone (4 zone özel alan belirleme)
- Alarm I/O: 4 giriş, 1 çıkış
- 24 V AC, maksimum 1.5 A (Isıtıcı dahil)
- Çalışma Isısı 0° - 40°C
- Ölçüler: Dome: 116.8(Ø) x 140(H)mm /
Muhafaza: 146(Ø) x 140(H)mm
- Ağırlık: 2 kg

SMB-23Z12F

12X Dahili Mini Speed Dome Kamera

Teknik Özellikler

Model	SBN - 23 Z 12 F
Signal System	PAL
Scanning System	2:1 Interlace
Scanning Frequency (H)	15.625 KHz
Scanning Frequency (V)	50 Hz
Image Sensor	1/4 Inch IT CCD
Total Pixels	795(H) x 596(V) 470K
Effective Pixels	752(H) x 582(V) 440K
Horizontal Resolution	550 TV Lines (B/W 600TV Lines)
Video Output Level	1.0V p-p (75Ω, Composite)
S/N Ratio	More than 52dB(AGC Off)
Lens	12x Optical, 3.68(W)mm~43.53(T)mm, F1.65(W) ~ F1.99(T)
Digital Zoom Ration	1x ~ 12x
Iris Control	Auto/Manual (0~100)
Panning/Tilting Ratio	Pan: 360° endless rotation; Tilt: 90
Panning/Tilting Speed	Manual: 0.1° ~ 360°/sec (Zoom Proportional)
Preset	127 position with Labels
Swing / Pattern / Group	8 Swings/4 Patterns (about 5min/Pattern)/8 groups (max. 20)
OSD	Multi-Language (English, Chinese, Spanish, Portuguese, Turkish, Russian, Czech, Korean)
Back Light	BLC / WDR / ECL / Off
Digital Slow Shutter	Off / Auto(x2~x128)
3D-DNR	Low / Middle / High / Off
White Balance	AWB / ATW / Manual (Red, Blue Gain, Adjustable)
Brightness Control	Adjustable (0~100)
Power-up Action	Resume the last action executed (Preset, Swing, Group)
Auto Parking / Flip	ON/OFF; Flip (Flips the image when the Tilt angle goes over 90°)
Auto Parking / Flip	4 Inputs, 1 Output
Operation Temp.	0~+40°C; -30~+50°C;(H

SMB-23Z12F

12X Dahili Mini Speed Dome Kamera

Electronic Shutter Speed	1/50~1/90,000sec.
Supplied Voltage	24VAC
Power Consumption	Max. 1.5A (Heater On)
Dimensions(ØxH)	Dome: 116.8(Ø) x 140(H)mm / Housing: 146(Ø) x 140(H)mm
Weight	Approx. 2.9Kg (with Wall Mount)